



Overview

- Simultaneously 12 Leads Acquisition
- 5 Inch HD LED Screen with Standard Grid Background
- Built-in print layout:
3x4, 3x4+1, 12x1
- External print /output layout:
3x4, 3x4+1,6x2 ,6x2+1,12x1
- Sampling Modes:
Real-time/Pre-sampling/Trigger sampling/ Period sampling
- Manual/Auto/Rhythm Modes
- Support Multiple Languages:
Simplified Chinese, English, Ukrainian, Turkish, Russian, French, Portuguese, Spanish, German, Italian, Polish, Romanian, Bulgarian, Croatian
- Format Report Storage:
ZQECG,PDF,PNG,XML,HL7,DICOM-WAVEFORM,DICOM-IMAGE,DICOM-PDF,GDT
- Alarm:
Electrode Disconnection
Recorder Unavailable
- Peripheral:
Support the machine to connect scanner, card reader and other patient information input device
- Support Wifi and cable connecting to the third party ECG network system, HIS and EMR system without ECG workstation
- Built-in Protection against Defibrillator
- Glasgow Algorithm :
Automatic measurement & analysis
- Support PACE Detection
- Freezing :
Max 60s waveform freezing and review function
- Heart Rate Detection Range: 30-350
- Rhythm analysis : 5 minutes

Technique Specification

Frequency Response: 0.01 ~ 350Hz

Time Constant: $\geq 3.2s$

Resolution : 800*480

Time Constant: $\geq 3.2s$

CMRR: $\geq 115dB$

Patient Leakage Current: $\leq 10\mu A$

Calibration Voltage : $1mV \pm 2\%$

Input Circuit: $\leq 50\mu A$

Input Impedance: $\geq 50 M\Omega(10 Hz)$

Noise Level: $\leq 15\mu Vp-p$

Sensitivity valve: $20 \mu V$

Polarization Voltage: $\pm 950mV$

A/D shift: 24 bits

Sampling rate : 32000Hz (1ms)

Sensitivity: 2.5, 5, 10, 20, 40 , Auto

Paper Speed: 5, 6.25,10,12.5, 25, 50mm/s

Recording Mode: Thermal array printer
8 dot/ mm (Vertical)
40 dot/ mm (Horizontal,
25mm/s)

Paper Type: Z-Fold Paper or Roll Paper

Paper Size: 80mm/20m

Filter Setting:

AC: off/50/60Hz;

EMG: off/25/35/45/75/100/150/250/350Hz;

Physical Specification

Dimension & weight:

Equipment:260mm × 180mm × 55mm

about 1.3 kg

Package: 420mm*330mm*250mm; 3.6kg

Electrical Power:

AC: 100V-240V, 50Hz/60Hz, 75VA

DC: Built-in Lithium Battery

Battery Capacity:

10.8V / 2200mAh

Continuous Operating:

AC $\geq 8h$ & DC $\geq 6h$

Recharge time:

The battery is charged to 90% for no more than 3 hours, and charged to 100% for no more than 3.5 hours

Data Storage:

Max. 2000 sets; support SD card, USB

Environmental Conditions:

Transportation Temperature:-20°C ~ +55°C

Relative Humidity:10% ~ 95%

Atmospheric Pressure: 50kpa ~ 106kpa

Operation Temperature:5°C ~ +40°C

Relative Humidity:20% ~ 85% (no condensation)

Atmospheric Pressure:57kPa ~ 106kPa

Storage Temperature:-20°C ~ +55°C

System Inputs & Outputs

2*USB2.0/ LAN/SD Card

Standard Package

iMAC 300 ECG Machine (with battery)

Patient Cable

Chest Electrodes

Limb Electrodes

Thermal Printing Paper

Power Cord

Grounding Wire

User Manual

Paper Roller

Optional Accessories

Series Electrodes

Thermal Printing Paper

Lithium Battery

Workstation Software

Trolley

Laser Printer

Paper Roller

Scanner

Card Reader

Suitcase

Wuhan Zoncare Bio-Medical Electronics Co., Ltd.

Add: 380,HIGH-TECH 2ND ROAD, EASTLAKE HIGH-TECH DEVELOPMENT, ZONE,WUHAN, HUBEI 430206, CHINA

Tel: +86-27-87770203 Email: info@zoncare.com

Fax: +86-27-87770581 Website: www.zoncare.com/en/

ZONcare

iMAC 300

Digital Three Channel ECG Machine

Advanced Function

- External laser printer to output the A4 report
- Scanner, card readers and other patient information input devices
- Wireless WiFi function
- GLASGOW ECG Algorithm can make precise diagnosis according to patient age, gender, racial taking medicine history, etc. especially for AMI, Ventricular Fibrillation, Ventricular Tachycardia, quarterly Bradycardia, malignant arrhythmia, etc.

Certificates

Quality Standards

ISO9001

ISO13485

CMD

CE

Design Standards

EN60601-1 & EN60601-1-2

EN60601-2-25

EN60601-1-4 & EN62304

EN ISO13485 & EN ISO10993-1

Wuhan Zoncare Bio-Medical Electronics Co., Ltd.

Add: 380,HIGH-TECH 2ND ROAD, EASTLAKE HIGH-TECH DEVELOPMENT, ZONE,WUHAN, HUBEI 430206, CHINA

Tel: +86-27-87770203 Email: info@zoncare.com

Fax: +86-27-87770581 Website: www.zoncare.com/en/